

---

# Material Safety Data Sheet

---

Product Name: **Green Indicating Liquid**

Product Part Number: **3642**

This product is a mixture of two or more chemicals as defined under O.S.H.A. standard 29 CFR 1910.1200. An individual MSDS for each chemical ingredient which comprises 1% or greater of the mixture (for Carcinogens concentrations of 0.1% or greater) is included with and is considered as part of the complete material safety data sheet.

## Chemical Ingredient No. 1

Common Name: ..... Mineral Seal Oil  
Chemical Name: ..... N/A  
Chemical Formula: ..... N/A  
Percent of Mixture (by volume): ..... 55 - 60%  
Manufacturer: ..... Ashland Chemical Co.  
MSDS: ..... Attached

## Chemical Ingredient No. 2

Common Name: ..... Diazene-42  
Chemical Family: ..... Brominated ethylbenzene isomers  
Percent of Mixture (by volume): ..... 40 - 45%  
Manufacturer: ..... Diaz Chemical Corp.  
MSDS: ..... Attached

## Chemical Ingredient No. 3

Common Name: ..... Kelly Green No. 32 Dye  
Percent of Mixture (by volume): ..... Less than 1%

The information herein is provided in good faith, but no warranty, either expressed or implied, is made by King Engineering Corporation.

**MATERIAL SAFETY  
DATA SHEET**

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

000842

**MINERAL SEAL OIL**

Page: 1

THIS MSDS COMPLIES WITH 29 CFR 1910.1200 (THE HAZARD COMMUNICATION STANDARD)

Product Name: MINERAL SEAL OIL  
CAS NUMBER: 64742-06-9

05 50 027 4962920-

Data Sheet No:	0000592-006
Prepared:	05/24/88
Supersedes:	11/17/87

KING ENGINEERING  
3201 SOUTH STATE STREET  
ANN ARBOR MI 48106

PRODUCT: 2524000  
INVOICE: 991688  
INVOICE DATE: 09/23/87  
TO: SAME

ATTN: PLANT MGR./SAFETY DIR.

**SECTION I PRODUCT IDENTIFICATION**

General or Generic ID: ALIPHATIC HYDROCARBON

DOT Hazard Classification: NOT APPLICABLE

**SECTION II-COMPONENTS**

IF PRESENT, IARC, NTP AND OSHA CARCINOGENS ARE IDENTIFIED IN THIS SECTION  
SEE DEFINITION PAGE FOR CLARIFICATION

INGREDIENT	% (by WT)	PEL	TLV	Note
ALIPHATIC PETROLEUM DISTILLATES CAS #: 64742-06-9	>95	5 MG/M3	5 MG/M3	

**SECTION III-PHYSICAL DATA**

Boiling Point	for PRODUCT	390.00 - 520.00 Deg F ( 198.88 - 271.11 Deg C ) @ 760.00 mm Hg
Vapor Pressure	for PRODUCT	< 0.01 mm Hg @ 68.00 Deg F ( 20.00 Deg C )
Specific Vapor Density		HEAVIER THAN AIR
Specific Gravity		.840 - .816 @ 60.00 Deg F ( 15.55 Deg C )
Percent Volatiles	NOT APPLICABLE	
Evaporation Rate	(N-BUTYL ACETATE = 1)	< .01

**SECTION IV-FIRE AND EXPLOSION INFORMATION**

FLASH POINT(COC ) 240.0 - 275.0 Deg F ( 115.6 - 135.0 Deg C )

EXPLOSIVE LIMIT (PRODUCT) LOWER - .9%

EXTINGUISHING MEDIA: REGULAR FOAM OR WATER FOG OR CARBON DIOXIDE OR DRY CHEMICAL

HAZARDOUS DECOMPOSITION PRODUCTS: MAY FORM TOXIC MATERIALS:, CARBON DIOXIDE AND CARBON MONOXIDE, VARIOUS HYDROCARBONS, ETC.

FIREFIGHTING PROCEDURES: WEAR SELF-CONTAINED BREATHING APPARATUS WITH A FULL FACEPIECE OPERATED IN THE POSITIVE PRESSURE DEMAND MODE WHEN FIGHTING FIRES.

SPECIAL FIRE &amp; EXPLOSION HAZARDS: NEVER USE WELDING OR CUTTING TORCH ON OR NEAR DRUM (EVEN EMPTY) BECAUSE PRODUCT (EVEN JUST RESIDUE) CAN IGNITE EXPLOSIVELY.

NFPA CODES: HEALTH- 0 FLAMMABILITY- 2 REACTIVITY- 0

**SECTION V-HEALTH HAZARD DATA**

PERMISSIBLE EXPOSURE LEVEL 5 MG/M3

THRESHOLD LIMIT VALUE 5 MG/M3

EFFECTS OF ACUTE OVEREXPOSURE: FOR PRODUCT

EYES - MAY CAUSE IRRITATION.  
SKIN - PROLONGED OR REPEATED CONTACT CAN CAUSE MODERATE IRRITATION, DEFATTING, DERMATITIS.  
BREATHING - OF MIST CAN CAUSE IRRITATION OF NASAL AND RESPIRATORY PASSAGES.  
SWALLOWING - CAN CAUSE GASTROINTESTINAL IRRITATION, NAUSEA, VOMITING, AND DIARRHEA. ASPIRATION OF MATERIAL INTO THE LUNGS CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

FIRST AID:

IF ON SKIN: THOROUGHLY WASH EXPOSED AREA WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING. LAUNDRY CONTAMINATED CLOTHING BEFORE RE-USE.

IF IN EYES: FLUSH WITH LARGE AMOUNTS OF WATER, LIFTING UPPER AND LOWER LIDS OCCASIONALLY, GET MEDICAL ATTENTION.

IF SWALLOWED: DO NOT INDUCE VOMITING, KEEP PERSON WARM, QUIET, AND GET MEDICAL ATTENTION. ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

IF BREATHED: IF AFFECTED, REMOVE INDIVIDUAL TO FRESH AIR. IF BREATHING IS DIFFICULT, ADMINISTER OXYGEN. IF

**MATERIAL SAFETY  
DATA SHEET****Ashland Chemical Company**

DIVISION OF ASHLAND OIL, INC.

P. O. BOX 2219, COLUMBUS, OHIO 43216 • (614) 889-3333

24-HOUR EMERGENCY TELEPHONE (606) 324-1133



000842

**MINERAL SEAL OIL**

Page: 2

**SECTION V-HEALTH HAZARD DATA (Continued)**

BREATHING HAS STOPPED GIVE ARTIFICIAL RESPIRATION. KEEP PERSON WARM, QUIET AND GET MEDICAL ATTENTION.

PRIMARY ROUTE(S) OF ENTRY:

SKIN CONTACT

EFFECTS OF CHRONIC OVEREXPOSURE: FOR PRODUCT

THIS PRODUCT IS A PARAFFINIC PETROLEUM OIL SIMILAR IN NATURE TO THE MINERAL SEAL OIL WHICH EXXON COMPANY REPORTED TO THE EPA UNDER SECTION 8(E) OF THE TOXIC SUBSTANCE CONTROL ACT. THE REPORT WAS SUBMITTED BASED ON AN ONGOING MOUSE SKIN PAINTING STUDY WHICH SHOWED 8 OF AN ORIGINAL 50 ANIMALS DEVELOPED OBSERVABLE SKIN TUMORS.

**SECTION VI-REACTIVITY DATA**

HAZARDOUS POLYMERIZATION: CANNOT OCCUR

STABILITY: STABLE

INCOMPATIBILITY: AVOID CONTACT WITH:, STRONG OXIDIZING AGENTS.

**SECTION VII-SPILL OR LEAK PROCEDURES**STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED:

SMALL SPILL: ABSORB LIQUID ON PAPER, VERMICULITE, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND TRANSFER TO HOOD.

LARGE SPILL: ELIMINATE ALL IGNITION SOURCES (FLARES, FLAMES INCLUDING PILOT LIGHTS, ELECTRICAL SPARKS). PERSONS NOT WEARING PROTECTIVE EQUIPMENT SHOULD BE EXCLUDED FROM AREA OF SPILL UNTIL CLEAN-UP HAS BEEN COMPLETED. STOP SPILL AT SOURCE, DIKE AREA OF SPILL TO PREVENT SPREADING, PUMP LIQUID TO SALVAGE TANK. REMAINING LIQUID MAY BE TAKEN UP ON SAND, CLAY, EARTH, FLOOR ABSORBENT, OR OTHER ABSORBENT MATERIAL AND SHOVELED INTO CONTAINERS.

WASTE DISPOSAL METHOD:

SMALL SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

LARGE SPILL: DISPOSE OF IN ACCORDANCE WITH ALL LOCAL, STATE AND FEDERAL REGULATIONS.

**SECTION VIII-PROTECTIVE EQUIPMENT TO BE USED**

RESPIRATORY PROTECTION: IF WORKPLACE EXPOSURE LIMIT(S) OF PRODUCT OR ANY COMPONENT IS EXCEEDED (SEE SECTION II), A NIOSH/MSHA APPROVED AIR SUPPLIED RESPIRATOR IS ADVISED IN ABSENCE OF PROPER ENVIRONMENTAL CONTROL. OSHA REGULATIONS ALSO PERMIT OTHER NIOSH/MSHA RESPIRATORS (NEGATIVE PRESSURE TYPE) UNDER SPECIFIED CONDITIONS (SEE YOUR SAFETY EQUIPMENT SUPPLIER). ENGINEERING OR ADMINISTRATIVE CONTROLS SHOULD BE IMPLEMENTED TO REDUCE EXPOSURE.

VENTILATION: PROVIDE SUFFICIENT MECHANICAL (GENERAL AND/OR LOCAL EXHAUST) VENTILATION TO MAINTAIN EXPOSURE BELOW TLV(S).

PROTECTIVE GLOVES: WEAR RESISTANT GLOVES SUCH AS:, POLYETHYLENE

EYE PROTECTION: CHEMICAL SPLASH GOGGLES IN COMPLIANCE WITH OSHA REGULATIONS ARE ADVISED; HOWEVER, OSHA REGULATIONS ALSO PERMIT OTHER TYPE SAFETY GLASSES. (CONSULT YOUR SAFETY EQUIPMENT SUPPLIER)

OTHER PROTECTIVE EQUIPMENT: TO PREVENT REPEATED OR PROLONGED SKIN CONTACT, WEAR IMPERVIOUS CLOTHING AND BOOTS.

**SECTION IX-SPECIAL PRECAUTIONS OR OTHER COMMENTS**

CONTAINERS OF THIS MATERIAL MAY BE HAZARDOUS WHEN EMPTIED. SINCE EMPTIED CONTAINERS RETAIN PRODUCT RESIDUES (VAPOR, LIQUID, AND/OR SOLID), ALL HAZARD PRECAUTIONS GIVEN IN THE DATA SHEET MUST BE OBSERVED.

THE INFORMATION ACCUMULATED HEREIN IS BELIEVED TO BE ACCURATE BUT IS NOT WARRANTED TO BE WHETHER ORIGINATING WITH THE COMPANY OR NOT. RECIPIENTS ARE ADVISED TO CONFIRM IN ADVANCE OF NEED THAT THE INFORMATION IS CURRENT, APPLICABLE, AND SUITABLE TO THEIR CIRCUMSTANCES.


**MATERIAL SAFETY  
DATA SHEET**

24-HOUR EMERGENCY TELEPHONE (606) 324-1133

**DEFINITIONS**

This definition page is intended for use with Material Safety Data Sheets supplied by the Ashland Chemical Company. Recipients of these data sheets should consult the OSHA Safety and Health Standards (29 CFR 1910), particularly subpart G - Occupational Health and Environmental Control, and subpart I - Personal Protective Equipment, for general guidance on control of potential Occupational Health and Safety Hazards.

**SECTION I**  
**PRODUCT IDENTIFICATION**

**GENERAL OR GENERIC ID:** Chemical family or product description.

**DOT HAZARD CLASSIFICATION:** Product meets DOT criteria for hazards listed.

**SECTION II**  
**COMPONENTS**

Components are listed in this section if they present a physical or health hazard and are present at or above 1% in the mixture. If a component is identified as a CARCINOGEN by NTP, IARC or OSHA as of the date on the MSDS, it will be listed and footnoted in this section when present at or above 0.1% in the product. Negative conclusions concerning carcinogenicity are not reported. Additional information may be found in Section V. Other components may be listed if deemed appropriate.

Identities of components listed generically are declared trade secret.

Exposure recommendations are for components. OSHA Permissible Exposure Limits (PELs) and American Conference of Governmental Industrial Hygienists (ACGIH) Threshold Limit Values (TLVs) appear on the line with the component identification. Other recommendations appear as footnotes.

**SECTION III**  
**PHYSICAL DATA**

**BOILING POINT:** Of product if known. The lowest value of the components is listed for mixtures.

**VAPOR PRESSURE:** Of product if known. The highest value of the components is listed for mixtures.

**SPECIFIC VAPOR DENSITY:** Compared to AIR = 1. If Specific Vapor Density of product is not known, the value is expressed as lighter or heavier than air.

**SPECIFIC GRAVITY:** Compared to WATER = 1. If Specific Gravity of product is not known, the value is expressed as less than or greater than water.

**pH:** If applicable.

**PERCENT VOLATILES:** Percentage of material with initial boiling point below 425 degrees Fahrenheit.

**EVAPORATION RATE:** Indicated as faster or slower than ETHYL ETHER, unless otherwise stated.

**SECTION IV**  
**FIRE AND EXPLOSION DATA**

**FLASH POINT:** Method identified.

**EXPLOSION LIMITS:** For product if known. The lowest value of the components is listed for mixtures.

**HAZARDOUS DECOMPOSITION PRODUCTS:** known or expected hazardous products resulting from heating, burning or other reactions.

**SECTION IV (cont.)**

**EXTINGUISHING MEDIA:** Following National Fire Protection Association criteria.

**FIREFIGHTING PROCEDURES:** Minimum equipment to protect firefighters from toxic products of vaporization, combustion or decomposition in fire situations. Other firefighting hazards may also be indicated.

**SPECIAL FIRE AND EXPLOSION HAZARDS:** States hazards not covered by other sections.

**NFPA CODES:** Hazard ratings assigned by the National Fire Protection Association.

**SECTION V**  
**HEALTH HAZARD DATA**

**PERMISSIBLE EXPOSURE LIMIT:** For product.

**THRESHOLD LIMIT VALUE:** For product.

**EFFECTS OF ACUTE OVEREXPOSURE:** Potential local and systemic effects due to single or short term overexposure to the eyes and skin or through inhalation or ingestion.

**EFFECTS OF CHRONIC OVEREXPOSURE:** Potential local and systemic effects due to repeated or long term overexposure to the eyes and skin or through inhalation or ingestion.

**FIRST AID:** Procedures to be followed when dealing with accidental overexposure.

**PRIMARY ROUTE OF ENTRY:** Based on properties and expected use.

**SECTION VI**  
**REACTIVITY DATA**

**HAZARDOUS POLYMERIZATION:** Conditions to avoid to prevent hazardous polymerization resulting in a large release of energy.

**STABILITY:** Conditions to avoid to prevent hazardous or violent decomposition.

**INCOMPATIBILITY:** Materials and conditions to avoid to prevent hazardous reactions.

**SECTION VII**  
**SPILL OR LEAK PROCEDURES**

Reasonable precautions to be taken and methods of containment, clean-up and disposal. Consult federal, state and local regulations for accepted procedures and any reporting or notification requirements.

**SECTION VIII**  
**PROTECTIVE EQUIPMENT TO BE USED**

Protective equipment which may be needed when handling the product.

**SECTION IX**  
**SPECIAL PRECAUTIONS OR OTHER COMMENTS**

Covers any relevant points not previously mentioned.

**ADDITIONAL COMMENTS**

Containers should be either reconditioned by CERTIFIED firms or properly disposed of by APPROVED firms. Disposal of containers should be in accordance with applicable laws and regulations. "EMPTY" drums should not be given to individuals. Serious accidents have resulted from the misuse of "EMPTIED" containers (drums, pails, etc.). Refer to Sections IV and IX.

**Material Safety Data Sheet**  
 May be used to comply with  
 OSHA's Hazard Communication Standard,  
 29 CFR 1910.1200. Standard must be  
 consulted for specific requirements.

**U.S. Department of Labor**  
 Occupational Safety and Health Administration  
 (Non-Mandatory Form)  
 Form Approved  
 OMB No. 1218-0072



**IDENTITY (As Used on Label and List)**  
 DIAZENE - 42

*Note: Blank spaces are not permitted. If any item is not applicable, or no information is available, the space must be marked to indicate that.*

**Section I**

N/A= Not Available

**Manufacturer's Name**  
 DIAZ CHEMICAL CORPORATION  
**Address (Number, Street, City, State, and ZIP Code)**  
 P.O. BOX 194  
 40 JACKSON STREET  
 HOLLEY, NEW YORK 14470

**Emergency Telephone Number**  
 (716) 638-6321  
**Telephone Number for Information**  
 (716) 638-6321  
**Date Prepared**  
 May 28, 1986  
**Signature of Preparer (optional)**  
*Marc S. MacClure*

**Section II — Hazardous Ingredients/Identity Information**

Hazardous Components (Specific Chemical identity: Common Name(s))	OSHA PEL	ACGIH TLV	Other Limits Recommended	% (optional)
BROMOETHYLBENZENES CAS# 1585-07-5	N/A	N/A	N/A	
DIBROMOETHYLBENZENES CAS# 30812-87-4	N/A	N/A	N/A	
TRIBROMOETHYLBENZENES CAS# 31195-17-2	N/A	N/A	N/A	

**Section III — Physical/Chemical Characteristics**

Boiling Point 390-580°F	200-300°C	Specific Gravity (H <sub>2</sub> O - 1) 15/15°C	1.73-1.75
Vapor Pressure (mm Hg.)	N/A	Melting Point less than 0°C	N/A
Vapor Density (AIR - 1)	9.4	Evaporation Rate (Butyl Acetate - 1)	less than
Solubility in Water Negligible			
Appearance and Odor Clear liquid, colorless to light yellow, mothball odor			

**Section IV — Fire and Explosion Hazard Data**

Flesh Point (Method Used) NONE, greater than 200°F	Flammable Limits N/A	LEL N/A	UEL N/A
Extinguishing Media WATER, CO <sub>2</sub> , CHEMICAL FOAM			
Special Fire Fighting Procedures NONE			
Unusual Fire and Explosion Hazards NONE			

**Section V — Reactivity Data**

Stability	Unstable		Conditions to Avoid Avoid contact with finely divided reducing metals, such as powdered aluminum
	Stable	X	

Incompatibility (*Materials to Avoid*) Avoid contact with finely divided reducing metals

Hazardous Decomposition or Byproducts Hydrogen Bromide, Carbon Monoxide, Carbon Dioxide

Hazardous polymerization	May Occur		Conditions to Avoid
	Will Not Occur	X	

**Section VI — Health Hazard Data**

Route(s) of Entry:	Inhalation? X	Skin? X	Ingestion? X
--------------------	------------------	------------	-----------------

Health Hazards (*Acute and Chronic*) INHALATION- Probable nasal irritation possible liver and kidney damage upon repeated or long term contact.

SKIN-May cause irritation

Carcinogenicity:	N/A	NTP? NO	IARC Monographs? NO	OSHA Regulated? NO
------------------	-----	------------	------------------------	-----------------------

Signs and Symptoms of Exposure Nasal or skin irritation

Medical Conditions Generally Aggravated by Exposure N/A

Emergency and First Aid Procedures SKIN-Wash with soap and water. EYE-Irrigate with large volumes of water. INGESTION-Induce vomiting. INHALATION-Remove to fresh air. See a physician.

**Section VII — Precautions for Safe Handling and Use**

Steps to Be Taken in Case Material is Released or Spilled Position pail or drum to minimize leak. Absorb spilled material in absorbant such as clay, or other appropriate material.

Waste Disposal Method LIQUID- Incineration at Hazardous Waste Incineration Facility  
SOLIDS (from spill clean-up)- Landfill at Secure Chemical Landfill

Precautions to Be Taken in Handling and Storing Practice reasonable care to avoid skin and eye contact and to avoid breathing vapors.

Other Precautions N/A

**Section VIII — Control Measures**

Respiratory Protection (*Specify Type*) Organic Vapor Cannister

Ventilation	Local Exhaust "Adequate" Ventilation	Special	N/A
	Mechanical ( <i>General</i> ) N/A	Other	N/A

Protective Gloves Rubber Gloves Eye Protection Safety Glasses

Other Protective Clothing or Equipment Coveralls